



Declaration of Performance

DoP-CPR- 100003000026-00040/2

1. Unique identification code of the product, product type or product family: Collection: LES TAPISSERIES Designs: Brocade Ramage Type: 06D References: 97840 - 97842 97830 - 97832																																															
2. Identification of the product: Type, batch or serial number: See packing label																																															
3. The product(s) are intended for use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15101-1 Wallcovering for decorative use																																															
4. Name and contact address of the manufacturer: Arte NV Industriezone "De Waerde" Senator A. Jeurissenlaan 1210 BE-3520 Zonhoven T +32 (0) 11 81 93 00 F +32 (0) 11 81 93 01 info.belgium@arte-international.com																																															
5. Name and contact address of authorised representative (distributor, importer): Not applicable																																															
6. System of assessment and verification of constancy of performance: System 3																																															
7. Notified testing laboratory Centexbel performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s): Certification report Centexbel : 20/1155																																															
8. Declared performance: <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 20%;">Essential Characteristic</th> <th style="width: 20%;">Performance</th> <th style="width: 10%;">Harmonised technical</th> <th style="width: 20%;">Essential Characteristic</th> <th style="width: 10%;">Performance</th> <th style="width: 10%;">Harmonised technical</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire EN 13501-1</td> <td>C-s1,d0</td> <td rowspan="7" style="text-align: center; vertical-align: middle;"> EN 15102:2007 A1:2011 </td> <td>Release of vinyl chloride monomer EN 12149-B</td> <td>< 0.2 mg/kg</td> <td rowspan="4" style="text-align: center; vertical-align: middle;"> EN 15102:2007 A1: 2011 </td> </tr> <tr> <td>Release of formaldehyde EN 12149-C</td> <td>< 120 mg / kg</td> <td></td> <td></td> </tr> <tr> <td rowspan="5">Release of heavy metals (EN 12149-A)</td> <td>Anitimony</td> <td>< 0.1 mg/kg</td> <td rowspan="5">Sound absorption ISO 354</td> <td rowspan="5">NPD</td> </tr> <tr> <td>Arcenic</td> <td>< 0.1 mg/kg</td> </tr> <tr> <td>Barium</td> <td>< 0.1 mg/kg</td> </tr> <tr> <td>Cadmium</td> <td>< 0.3 mg/kg</td> </tr> <tr> <td>Chromium</td> <td>< 0.1 mg/kg</td> </tr> <tr> <td></td> <td>Lead</td> <td>< 0.5 mg/kg</td> <td rowspan="2">Thermal resistance "EN 12524" or "EN12667"</td> <td rowspan="2">NPD</td> </tr> <tr> <td></td> <td>Mercury</td> <td>< 0.1 mg/kg</td> </tr> <tr> <td></td> <td>Selenium</td> <td>< 1.0 mg/kg</td> <td></td> <td></td> </tr> </tbody> </table>						Essential Characteristic	Performance	Harmonised technical	Essential Characteristic	Performance	Harmonised technical	Reaction to fire EN 13501-1	C-s1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011	Release of formaldehyde EN 12149-C	< 120 mg / kg			Release of heavy metals (EN 12149-A)	Anitimony	< 0.1 mg/kg	Sound absorption ISO 354	NPD	Arcenic	< 0.1 mg/kg	Barium	< 0.1 mg/kg	Cadmium	< 0.3 mg/kg	Chromium	< 0.1 mg/kg		Lead	< 0.5 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD		Mercury	< 0.1 mg/kg		Selenium	< 1.0 mg/kg		
Essential Characteristic	Performance	Harmonised technical	Essential Characteristic	Performance	Harmonised technical																																										
Reaction to fire EN 13501-1	C-s1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011																																										
Release of formaldehyde EN 12149-C	< 120 mg / kg																																														
Release of heavy metals (EN 12149-A)	Anitimony		< 0.1 mg/kg	Sound absorption ISO 354		NPD																																									
	Arcenic		< 0.1 mg/kg																																												
	Barium		< 0.1 mg/kg																																												
	Cadmium		< 0.3 mg/kg																																												
	Chromium		< 0.1 mg/kg																																												
	Lead	< 0.5 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD																																											
	Mercury	< 0.1 mg/kg																																													
	Selenium	< 1.0 mg/kg																																													
* NPD: No Performance Declared																																															
Signed for and behalf of the manufacturer or authorised representative by: 2-Apr-26 Philippe Desart Managing Director																																															