

Declaration of Performance

DoP-CPR- 100003000026-00040/2

1. Unique identification code of the product, product type or product family: <table style="width: 100%;"> <tr> <td style="width: 33%;">Collection:</td> <td style="width: 33%;">LES TAPISSERIES</td> <td style="width: 33%;">Type:</td> <td style="width: 33%;">06D</td> </tr> <tr> <td>Designs:</td> <td></td> <td>References:</td> <td></td> </tr> <tr> <td>Brocade</td> <td></td> <td>97840 - 97842</td> <td></td> </tr> <tr> <td>Ramage</td> <td></td> <td>97830 - 97832</td> <td></td> </tr> </table>						Collection:	LES TAPISSERIES	Type:	06D	Designs:		References:		Brocade		97840 - 97842		Ramage		97830 - 97832																															
Collection:	LES TAPISSERIES	Type:	06D																																																
Designs:		References:																																																	
Brocade		97840 - 97842																																																	
Ramage		97830 - 97832																																																	
2. Identification of the product: Type, batch or serial number: See packing label																																																			
3. The product(s) are intended for use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15101-1 Wallcovering for decorative use																																																			
4. Name and contact address of the manufacturer: Arte NV Industriezone "De Waerde" Senator A. Jeurissenlaan 1210 BE-3520 Zonhoven T +32 (0) 11 81 93 00 F +32 (0) 11 81 93 01 info.belgium@arte-international.com																																																			
5. Name and contact address of authorised representative (distributor, importer): Not applicable																																																			
6. System of assessment and verification of constancy of performance: System 3																																																			
7. Notified testing laboratory Centexbel performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s): Certification report Centexbel : 20/1155																																																			
8. Declared performance: <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width: 25%;">Essential Characteristic</th> <th style="width: 25%;">Performance</th> <th style="width: 10%;">Harmonised technical</th> <th style="width: 25%;">Essential Characteristic</th> <th style="width: 10%;">Performance</th> <th style="width: 15%;">Harmonised technical</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire EN 13501-1</td> <td>C-s1,d0</td> <td rowspan="7" style="text-align: center; vertical-align: middle;"> EN 15102:2007 A1:2011 </td> <td>Release of vinyl chloride monomer EN 12149-B</td> <td>< 0.2 mg/kg</td> <td rowspan="4" style="text-align: center; vertical-align: middle;"> EN 15102:2007 A1: 2011 </td> </tr> <tr> <td>Release of formaldehyde EN 12149-C</td> <td>< 120 mg / kg</td> <td></td> <td></td> </tr> <tr> <td rowspan="5">Release of heavy metals (EN 12149-A)</td> <td>Antimony < 0.1 mg/kg</td> <td>Sound absorption ISO 354</td> <td>NPD</td> </tr> <tr> <td>Arcenic < 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Barium < 0.1 mg/kg</td> <td>Thermal resistance "EN 12524" or "EN12667"</td> <td>NPD</td> </tr> <tr> <td>Cadmium < 0.3 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Chromium < 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Lead < 0.5 mg/kg</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Mercury < 0.1 mg/kg</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Selenium < 1.0 mg/kg</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						Essential Characteristic	Performance	Harmonised technical	Essential Characteristic	Performance	Harmonised technical	Reaction to fire EN 13501-1	C-s1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011	Release of formaldehyde EN 12149-C	< 120 mg / kg			Release of heavy metals (EN 12149-A)	Antimony < 0.1 mg/kg	Sound absorption ISO 354	NPD	Arcenic < 0.1 mg/kg			Barium < 0.1 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD	Cadmium < 0.3 mg/kg			Chromium < 0.1 mg/kg			Lead < 0.5 mg/kg				Mercury < 0.1 mg/kg					Selenium < 1.0 mg/kg				
Essential Characteristic	Performance	Harmonised technical	Essential Characteristic	Performance	Harmonised technical																																														
Reaction to fire EN 13501-1	C-s1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011																																														
Release of formaldehyde EN 12149-C	< 120 mg / kg																																																		
Release of heavy metals (EN 12149-A)	Antimony < 0.1 mg/kg		Sound absorption ISO 354	NPD																																															
	Arcenic < 0.1 mg/kg																																																		
	Barium < 0.1 mg/kg		Thermal resistance "EN 12524" or "EN12667"	NPD																																															
	Cadmium < 0.3 mg/kg																																																		
	Chromium < 0.1 mg/kg																																																		
Lead < 0.5 mg/kg																																																			
Mercury < 0.1 mg/kg																																																			
Selenium < 1.0 mg/kg																																																			
* NPD: No Performance Declared																																																			
Signed for and behalf of the manufacturer or authorised representative by: 2-Apr-26 Philippe Desart Managing Director																																																			