

Declaration of Performance

DoP-CPR- 25-2056

1. Unique identification code of the product, product type or product family: <table style="width: 100%;"> <tr> <td style="width: 40%;">Collection: Flamant Honoré</td> <td style="width: 60%;">Type: 01</td> </tr> <tr> <td>Designs: Lin</td> <td>References: 78030 - 78052 + 18202A - 78028A</td> </tr> <tr> <td>Lin Normandie</td> <td>78200 - 78234</td> </tr> <tr> <td>Terra de Lin</td> <td>78250 - 78281</td> </tr> </table>						Collection: Flamant Honoré	Type: 01	Designs: Lin	References: 78030 - 78052 + 18202A - 78028A	Lin Normandie	78200 - 78234	Terra de Lin	78250 - 78281																																									
Collection: Flamant Honoré	Type: 01																																																					
Designs: Lin	References: 78030 - 78052 + 18202A - 78028A																																																					
Lin Normandie	78200 - 78234																																																					
Terra de Lin	78250 - 78281																																																					
2. Identification of the product: Type, batch or serial number: See packing label																																																						
3. The product(s) are intended for use as wall covering(s) within a building according to the manufacturer's specifications and installation practices in accordance with EN 15101-1 Wallcovering for decorative use																																																						
4. Name and contact address of the manufacturer: Arte NV Industriezone "De Waerde" Senator A. Jeurissenlaan 1210 BE-3520 Zonhoven T +32 (0) 11 81 93 00 F +32 (0) 11 81 93 01 info.belgium@arte-international.com																																																						
5. Name and contact address of authorised representative (distributor, importer): Not applicable																																																						
6. System of assessment and verification of constancy of performance: System 3																																																						
7. Notified testing laboratory Centexbel performed the determination of the product type on the basis of type testing (based on sampling carried out by the manufacturer) and issued the test report(s): Certification report Centexbel : 19/721																																																						
8. Declared performance: <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width: 20%;">Essential Characteristic</th> <th style="width: 20%;">Performance</th> <th style="width: 10%;">Harmonised technical specification</th> <th style="width: 20%;">Essential Characteristic</th> <th style="width: 20%;">Performance</th> <th style="width: 10%;">Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire EN 13501-1</td> <td>B-S1,d0</td> <td rowspan="7" style="text-align: center; vertical-align: middle;"> EN 15102:2007 A1:2011 </td> <td>Release of vinyl chloride monomer EN 12149-B</td> <td style="text-align: center;">< 0.2 mg/kg</td> <td rowspan="7" style="text-align: center; vertical-align: middle;"> EN 15102:2007 A1: 2011 </td> </tr> <tr> <td>Release of formaldehyde EN 12149-C</td> <td style="text-align: center;">< 120 mg / kg</td> <td></td> <td></td> </tr> <tr> <td rowspan="5">Release of heavy metals (EN 12149-A)</td> <td>Antimony</td> <td style="text-align: center;">< 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Arsenic</td> <td style="text-align: center;">< 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Barium</td> <td style="text-align: center;">< 0.1 mg/kg</td> <td>Sound absorption ISO 354</td> <td style="text-align: center;">NPD</td> </tr> <tr> <td>Cadmium</td> <td style="text-align: center;">< 0.3 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Chromium</td> <td style="text-align: center;">< 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Lead</td> <td style="text-align: center;">< 0.5 mg/kg</td> <td>Thermal resistance "EN 12524" or "EN12667"</td> <td style="text-align: center;">NPD</td> </tr> <tr> <td>Mercury</td> <td style="text-align: center;">< 0.1 mg/kg</td> <td></td> <td></td> </tr> <tr> <td>Selenium</td> <td style="text-align: center;">< 1.0 mg/kg</td> <td></td> <td></td> </tr> </tbody> </table>						Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification	Reaction to fire EN 13501-1	B-S1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011	Release of formaldehyde EN 12149-C	< 120 mg / kg			Release of heavy metals (EN 12149-A)	Antimony	< 0.1 mg/kg			Arsenic	< 0.1 mg/kg			Barium	< 0.1 mg/kg	Sound absorption ISO 354	NPD	Cadmium	< 0.3 mg/kg			Chromium	< 0.1 mg/kg			Lead	< 0.5 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD	Mercury	< 0.1 mg/kg			Selenium	< 1.0 mg/kg		
Essential Characteristic	Performance	Harmonised technical specification	Essential Characteristic	Performance	Harmonised technical specification																																																	
Reaction to fire EN 13501-1	B-S1,d0	EN 15102:2007 A1:2011	Release of vinyl chloride monomer EN 12149-B	< 0.2 mg/kg	EN 15102:2007 A1: 2011																																																	
Release of formaldehyde EN 12149-C	< 120 mg / kg																																																					
Release of heavy metals (EN 12149-A)	Antimony		< 0.1 mg/kg																																																			
	Arsenic		< 0.1 mg/kg																																																			
	Barium		< 0.1 mg/kg	Sound absorption ISO 354		NPD																																																
	Cadmium		< 0.3 mg/kg																																																			
	Chromium		< 0.1 mg/kg																																																			
Lead	< 0.5 mg/kg	Thermal resistance "EN 12524" or "EN12667"	NPD																																																			
Mercury	< 0.1 mg/kg																																																					
Selenium	< 1.0 mg/kg																																																					

* NPD: No Performance Declared

Signed for and behalf of the manufacturer or authorised representative by:

10-Feb-25

Philippe Desart



Managing Director